



EC Series Self Contained Gourmet Ice Machines — with Progressive Water Discharge — up to 74kg

ECM 127 AS OX Medium gourmet cube 20g, Ø30mm x 34mm



Medium gourmet cube 20g, 30mm dia x H 34mm



Note: Ice production rate is measured with the water temperature at 10°C and an ambient temperature of 21°C.

- Up to 74kg daily production rate
- 39kg storage bin capacity
- · Air cooled version
- Produces individual transparent Gourmet crystal clear supercubes
- · Hydrocarbons R290 refrigerant gas
- XSafe Natural Sanitation System
- PWD-Progressive water discharge: pumps excess residual water up to a distance up to 15 meters
- Agion Technology resists the growth of microbes and the development of unpleasant odours
- Simple, reliable electromechanic controls
- Horizontal ice evaporator spray-system technology
- · Resistant stainless steel exterior
- Front access condenser air filter, removable and washable

- Routine maintenance visible alarm light on front panel
- Ergonomically designed ice storage access with disappearing door and door closing movement dampening system
- Includes removable air filter, ice scoop, water and drain hose

















EC Series Self Contained Gourmet Ice Machines – with Progressive Water Discharge – up to 74kg


ECM 127 AS OX











231 1 (3) 2

515

591

3

∢ j

moffat.com.au

Australia Moffat Pty Limited

Victoria/Tasmania

740 Springvale Road Mulgrave, Victoria 3170 Telephone 03-9518 3888 Facsimile 03-9518 3833 vsales@moffat.com.au

New South Wales Telephone 02-8833 4111 nswsales@moffat.com.au

South Australia Telephone 03-9518 3888 vsales@moffat.com.au

Queensland

Telephone 07-3630 8600 qldsales@moffat.com.au

Western Australia Telephone 08-9413 2400 wasales@moffat.com.au

UNIT OF MEASUREMENT: mm

- 1. 25/32" OD OVERFLOW DRAIN
- 2. 3/4" GAS WATER INLET
- 3. 3/4" GAS WATER OUTLET WATER COOLED UNIT ONLY
- 4. 3/4" GAS WATER INLET WATER COOLED UNIT ONLY
- 5. CORD SET

Ice production per 24 hours

Ambient temperature / Water temperature

10°C / 10°C	21°C / 10°C	32°C / 21°C
75	74	60

Dimensions

Width: 680mm 600mm Depth:

1009mm (including legs) Height:

Nett weight: 67kg Packed weight:

Water consumption

Air cooled version: 7.4 litres per hour

Electrical rating

Air cooled version: 230-240V, 1P+N+E, 50Hz, 670W,

10A cordset supplied

No Circuit wire: Compressor: 1400W Energy consumption: 12.9kW/hr

Refrigerant type

R290

Installation distance from wall

Rear 100mm Sides 150mm

Operating requirement air temperature 10-43°C

Water connection requirements

Inlet connection: R 3/4" 5-38°C Cold water: Pressure: 100-500kPa Water outlet connection: Ø3/4"

Important Notice:

Models and specifications are subject to change without notice. This spec sheet is meant for commercial purpose only. For technical documentation please refer to our service manuals



© Copyright Moffat Ltd